



US005528118A

United States Patent [19]

[11] Patent Number: **5,528,118**

Lee

[45] Date of Patent: **Jun. 18, 1996**

[54] GUIDELESS STAGE WITH ISOLATED REACTION STAGE

[75] Inventor: **Martin E. Lee**, Saratoga, Calif.

[73] Assignee: **Nikon Precision, Inc.**, Belmont, Calif.

[21] Appl. No.: **221,375**

[22] Filed: **Apr. 1, 1994**

[51] Int. Cl.⁶ **G03B 41/16**

[52] U.S. Cl. **318/568.17; 318/38; 74/479.01**

[58] Field of Search **318/560-575, 318/640, 38, 135; 74/479.01, 480 R, 490.07-1; 108/137-148; 248/638, 651, 656, 657; 269/55, 56, 58, 71; 250/492.1, 492.2, 492.22**

[56] References Cited

U.S. PATENT DOCUMENTS

Re. 27,289	2/1972	Sawyer	318/38
Re. 27,436	7/1972	Sawyer	346/29
3,789,285	1/1974	Nishizawa	318/687
3,889,164	6/1975	Nishizawa et al.	318/640
3,935,486	1/1976	Nagashima	310/12
4,019,109	4/1977	McCoy et al.	318/640
4,087,729	5/1978	Yamazaki et al.	318/601
4,129,291	12/1978	Kato et al.	269/71
4,234,175	6/1985	Imahashi et al.	318/649
4,392,642	7/1983	Chitayat	269/73
4,409,860	10/1983	Moriyama et al.	248/479
4,425,508	1/1984	Lewis, Jr. et al.	250/442.1
4,443,743	4/1984	Forys et al.	318/115
4,485,339	11/1984	Trost	318/640
4,492,356	1/1985	Taniguchi et al.	248/346
4,504,144	12/1985	Trost	356/150
4,506,204	3/1985	Galburt	318/653
4,506,205	3/1985	Trost et al.	318/653
4,507,597	3/1985	Trost	318/653
4,514,858	4/1985	Novak	378/34
4,516,253	5/1985	Novak	378/34
4,525,659	6/1985	Imahashi et al.	318/649
4,575,942	3/1986	Moriyama	33/1 M
4,615,515	10/1986	Suzuta et al.	269/73
4,628,238	12/1986	Smulders et al.	318/653
4,630,942	12/1986	Tsumaki et al.	384/8
4,641,071	2/1987	Tazawa et al.	318/640
4,648,723	3/1987	Sugiyama et al.	384/9

4,648,724	3/1987	Sugiyama et al.	384/9
4,653,408	3/1987	Nagashima et al.	108/20
4,654,571	3/1987	Hinds	318/687
4,667,139	5/1987	Hirai et al.	318/687
4,675,891	6/1987	Plessis et al.	378/132
4,677,651	6/1987	Hartl et al.	378/132
4,684,315	8/1987	Sugishima et al.	414/749

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

63-20014 4/1988 Japan .

OTHER PUBLICATIONS


Japan Society Precision Engineering, vol. 22, No. 1, Moriyama, et al., pp. 13-17, Mar. 1988.

Primary Examiner—Brian Sircus
Attorney, Agent, or Firm—Skjervens, Morrill, MacPherson, Franklin & Friel; Norman R. Klivans

[57] ABSTRACT

A guideless stage for aligning a wafer in a microlithography system is disclosed, and a reaction frame is disclosed which isolates both external vibrations as well as vibrations caused by reaction forces from an object stage. In the guideless stage an object stage is disclosed for movement in at least two directions and two separate and independently movable followers move and follow the object stage and cooperating linear force actuators are mounted on the object stage and the followers for positioning the object stage in the first and second directions. The reaction frame is mounted on a base structure independent of the base for the object stage so that the object stage is supported in space independent of the reaction frame. At least one follower is disclosed having a pair of arms which are respectively movable in a pair of parallel planes with the center of gravity of the object stage therebetween. The linear positioning forces of the actuator drive means are mounted and controlled so that the vector sum of the moments of force at the center of gravity of the object stage due to the positioning forces of the drive means is substantially equal to zero. The actuator mounting means can include at least two thin flexible members mounted in series with the primary direction of flex of the members being orthogonal to one another.

14 Claims, 11 Drawing Sheets



U.S. PATENT DOCUMENTS

4,687,980	8/1987	Phillips et al.	318/640	4,916,340	4/1990	Negishi	310/12
4,698,575	10/1987	Bouwer	318/640	4,952,858	8/1990	Galburt	318/560
4,708,465	11/1987	Isohata et al.	355/53	5,022,619	6/1991	Mamada	248/178
4,723,086	2/1988	Leibovich et al.	310/328	5,040,431	8/1991	Sakino et al.	74/479
4,742,286	5/1988	Phillips	318/640	5,059,090	10/1991	Bobroff et al.	414/749
4,744,675	5/1988	Sakino et al.	384/12	5,120,034	6/1992	Van Engelen et al.	269/73
4,750,721	6/1988	Sasada	269/73	5,150,153	9/1992	Franken et al.	355/53
4,770,531	9/1988	Tanaka et al.	356/358	5,228,358	7/1993	Sakino et al.	74/479 R
4,812,725	3/1989	Chitayat	318/625	5,241,183	8/1993	Kanai et al.	250/453.11
4,817,930	4/1989	Van Deuren	269/73	5,243,491	9/1993	Van Eijk et al.	361/144
4,870,668	9/1989	Frankel et al.	378/34	5,280,677	1/1994	Kubo et al.	33/568
4,887,804	12/1989	Ohtsuka	269/73	5,285,142	2/1994	Galburt et al.	318/640
				5,327,060	7/1994	Van Engelen et al.	318/640




FIG. 1




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 3A




FIG. 4




FIG. 4A




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

GUIDELESS STAGE WITH ISOLATED REACTION STAGE

FIELD OF INVENTION

The present invention relates, in general, to electro-mechanical alignment and isolation and, more particularly, to such method and apparatus for supporting and aligning a wafer in a microlithographic system and isolating the system from its own reaction forces and external vibrations.

BACKGROUND OF THE INVENTION

Various support and positioning structures are known for use in microlithographic instruments. Typically, in the prior art, XY guides, including a separate X guide assembly and Y guide assembly, are utilized with one guide assembly mounted on and, movable with the other guide assembly. Often, a separate wafer stage is mounted on top of these guide assemblies. These structures require high precision and many parts. Typically, external forces directed to parts of the positioning assembly and reaction forces due to movement of different parts of the assembly are coupled directly to the image forming optics and reticle handling equipment resulting in unwanted vibration.

U.S. Pat. No. 5,120,036 to Van Engelen et al. describes a two-step positioning device using Lorentz forces and a static gas bearing for an opto-lithographic device.

U.S. Pat. No. 4,952,858 is directed to a microlithographic apparatus utilizing electro-magnetic alignment apparatus including a monolithic stage, a sub-stage and isolated reference structure in which force actuators imposed between the monolithic stage and the sub-stage are used for suspending and positioning the monolithic stage in space. In this apparatus a Y frame or stage is mounted on an X frame and the monolithic stage is positioned from and supported in space from the Y frame.

SUMMARY OF THE INVENTION

Broadly stated, the present invention is directed to method and apparatus utilizing a guideless stage for supporting an article and incorporating a reaction frame which isolates both external forces as well as reaction forces created in moving the object from other elements of the system such as a lens system which produces an image that is exposed on the photoresist of a wafer object surface.

The present invention incorporates an object stage, a reaction frame mounted on a base and substantially free from transferring vibrations between itself and the object stage, means for supporting the object stage in space independent of the reaction frame and cooperating force type linear actuator means mounted on the object stage and the reaction frame for positioning of the object stage. The object stage can be mounted for movement in a given direction or can constitute a XY stage for movement in the X and Y directions while being supported in space in the Z direction.

A feature, an advantage of this invention is the provision of a support, positioning and isolation assembly which allows the positioning function of the object or wafer stage to be accomplished while minimizing vibrations coupled to the stage and lens systems from the reaction stage faster and with fewer parts while minimizing vibrations coupled to the stage and isolating the stage from undesired reaction forces.

In accordance with another aspect of the present invention, a positioning method and apparatus are provided for an XY stage with an independently moveable X follower and

independently moveable Y follower and cooperating linear force actuators mounted between the stage and followers whereby the movement of either follower does not effect the movement of the other follower.

Another aspect of this invention is the provision on at least one follower of a pair of arms on the follower with each arm supporting a drive member and wherein the arms are positioned and movable in spaced apart planes above and below the center of gravity of the object stage.

In accordance with another aspect of the present invention, the guideless stage incorporates at least three linear force actuators with two of those actuators driving in one of the X or Y directions and the third actuators driving in the other of the X and Y directions. In accordance with the preferred embodiment of this invention the guideless stage incorporates at least four linear actuators operating between the XY stage and a reaction frame assembly with each actuator including a drive member on the XY stage so that a pair of X drive members serve to drive the XY stage in an X direction and a pair of Y drive members serve to drive the XY stage in the Y direction. The linear actuators and their drive members are constructed, positioned and controlled such that the vector sum of the moments of force at the center of gravity of the XY stage due to the positioning forces of cooperating drive members is substantially equal to zero.

These features and advantages of the present invention will become more apparent upon perusal of the following specification taken in conjunction with the following drawing wherein similar characters of reference refer to similar parts in each of the several views.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a microlithography system incorporating the present invention.

FIG. 1A is a view of a portion of the structure shown in FIG. 1 delineated by line A—A and with the reaction stage which is shown FIG. 1 removed.

FIG. 1B is an elevational view, partially in section, of the structure shown in FIG. 1.

FIG. 1C is a schematic elevational view, partially in section, of the object positioning apparatus of the present invention.

FIG. 2 is a plan view of the wafer XY stage position above the reaction stage.

FIG. 3 is a side elevational view of a portion of the structure shown in FIG. 2 taken along line 3—3 in the direction of the arrows.

FIG. 3A is an enlarged view of a portion of the structure shown in FIG. 3 delineated by line B—B.

FIG. 4 is a perspective view of the reaction stage showing the XY followers without the means for coupling to the XY stage for positioning of the XY stage.

FIG. 4A is an enlarged perspective view of the XY followers illustrated in FIG. 4.

FIG. 5 is a schematic block diagram of the position sensing and control system for the preferred embodiment of this invention.

FIGS. 6 and 7 are views similar to FIGS. 2 and 3 of an alternative embodiment of the present invention.

FIGS. 8 and 9 are views similar to FIGS. 2 and 3 of still another embodiment of the present invention.

FIG. 10 is an enlarged top view of a portion of the structure shown in FIG. 8.

FIG. 11 is an end view of the structure shown in FIG. 10 taken along line 11—11 in the direction of the arrows.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

While it will be appreciated by those skilled in the art that the guideless stage, with or without its isolating reaction frame, has many applications to many different types of instruments for precise positioning of objects, the present invention will be described with respect to a preferred embodiment in the form of a microlithographic instrument for aligning wafers in a system where a lens produces an image which is exposed to the photoresist on the wafer surface. In addition, while the guideless stage with or without its isolation stage can be utilized as a guideless object stage movable in just one direction, such as a X or a Y direction, the preferred embodiment is directed to a guideless XY wafer stage as described below.

Referring now to the drawings, with particular reference to FIGS. 1 and 2, there is shown a photolithographic instrument 10 having an upper optical system 12 and a lower wafer support and positioning system 13. The optical system 12 includes an illuminator 14 including a lamp LMP, such as a mercury lamp, and an ellipsoid mirror EM surrounding the lamp LPM. And the illuminator 14 comprises optical integrator such as a fly's eye lens FEL producing secondary light source images and a condenser lens CL for illuminating a reticle (mask) R with uniformed light flux. A mask holder RST holding the mask R is mounted above a lens barrel PL of a projection optical system 16. The lens barrel PL is fixed on a part of a column assembly which is supported on a plurality of rigid arms 18 each mounted on the top portion of an isolation pad or block system 20.

Inertial or seismic blocks 22 are located on the system such as mounted on the arms 18. These blocks 22 can take the form of a cast box which can be filled with sand at the operation site to avoid shipment of a massive structure. An object or wafer stage base 28 is supported from the arms 18 by depending blocks 22 and depending bars 26 and horizontal bars 27 (see FIG. 1A). FIG. 1B is an elevational view, partially in section, of the structure shown in FIG. 1 except that in FIG. 1B the blocks 22 are shown as being a different configuration than in FIGS. 1 and 1A.

Referring now to FIGS. 2 and 3, there are shown plan and elevational views, respectively, of the wafer supporting and positioning apparatus above the object or wafer stage base 28 including the object or wafer or XY stage 30 and the reaction frame assembly 60. The XY stage 30 includes a support plate 32 on which the wafer 34, such as a 12 inch wafer, is supported. The plate 32 is supported in space above the object stage base 28 via vacuum pre-load type air bearings 36 which can be controlled to adjust Z, i.e., tilt roll and focus. Alternatively, this support could employ combinations of magnets and coils.

The XY stage 30 also includes an appropriate element of a magnetic coupling means such as a linear drive motor for aligning the wafer with the lens of the optical system 16 for precisely positioning an image for exposure of a photoresist on the wafer's surface. In the embodiment illustrated, the magnetic coupling means takes the form of a pair of drive members such as X drive coils 42X and 42X' for positioning the XY stage 30 in the X direction and a pair of Y drive members such as drive coils 44Y and 44Y' for positioning the XY stage 30 in the Y direction. The associated portion of the magnetic coupling means on the reaction frame assembly 60 will be described in later detail below.

The XY stage 30 includes a pair of laser mirrors 38X operative with respect to a pair of laser beams 40A/40A' and 38Y operative with respect to a pair of laser beams 40B/40B'

of a laser beam interferometer system 92 for determining and controlling the precise XY location of the XY stage relative to a fixed mirror RMX at the lower part of the lens barrel PL of the projection optical system 16.

Referring to FIGS. 4 and 4A, the reaction frame assembly 60 has a reaction frame 61 which includes a plurality of support posts 62 which are mounted on the ground or a separate base substantially free from transferring vibrations between itself and the object stage.

The reaction frame 61 includes face plates 64X and 64X' extending between support posts 62 in the X direction and 66Y and 66Y' extending between support posts in the Y direction. Inside the face plates 64—66 a plurality of reaction frame rails 67—69 and 67'—69' are provided for supporting and guiding an X follower 72 and a Y follower 82. Inside face plate 64X are an upper follower guide rail 67 and a lower follower guide rail 68 (not shown) and on the inside surface of the opposite face plate 64X' are upper and lower follower guide rails 67' and 68'. On the inside surfaces of each of the face plates 66Y and 66Y' is a single guide rail 69 and 69', respectively, which is positioned vertically in between the guide rails 67 and 68.

The X follower includes a pair of spaced apart arms 74 and 74' connected at their one end by a cross piece 76. Drive elements such as drive tracks 78 and 78' (see FIG. 2) are mounted on the arms 74 and 74', respectively, for cooperating with the drive elements 42X and 42X' of the XY stage. Since in the illustrated embodiment the drive elements 42X and 42X' on the XY stage are shown as drive coils, the drive tracks on the X follower 72 take the form of magnets. The coupling elements could be reversed so that the coils would be mounted on the X follower and the magnets mounted on the XY stage. As the XY stage is driven in the X and Y direction, the laser interferometer system 92 detects the new position of the XY stage momentarily and generates a position information (X coordinate value). As described in greater detail below with reference to FIG. 5, a servo position control system 94 under control of a host processor (CPU) 96 controls the position of the X follower 72 and the y follower 82 in response to the position information from the interferometer system 92 to follow the XY stage 30 without any connection between the drive coils 42X, 42X' and the tracks 74, 74'.

For movably mounting the X follower 72 on the reaction frame 61, the ends of the arms 74 and 74' at the side of the reaction frame 61 ride or are guided on the rail 69, and the opposite ends of the arms 74 and 74' ride on rail 69' adjacent face plate 66 Y'. For moving the X follower 72 a drive member 77 is provided on the cross piece 76 for cooperating with the reaction frame guide 69 for moving the follower 72 in a direction which is perpendicular to the X direction of the XY stage. Since the precision drive and control takes place in the XY stage 30, the positioning control of the X follower 72 does not have to be as accurate and provide as close tolerances and air gaps as the XY stage 30. Accordingly, the drive mechanism 77 can be made of a combination of a screw shaft rotated by a motor and a nut engaged by the X follower 72 or a combination of a coil assembly and a magnet assembly to establish a linear motor and each combination can be further combined with a roller guiding mechanism.

Similar to the X follower 72, the Y follower 82 includes a pair of arms 84 and 84' connected at their one end by a crossbar 86 and including drive tracks 88 and 88' for cooperating with the Y drive members 44Y and 44Y'. The arms 84 and 84' of the Y follower 82 are guided on separate

guide rails. The ends of arm **84** ride or are guided on the upper rails **67** and **67'** and the ends of arm **84'** are guided on lower rails **68** and **68'**. A drive mechanism **87** is provided on the cross piece **86** of the Y follower **82** for moving the Y follower **82** along guides **67**, **67'**, **68** and **68'** between the face plates **66Y** and **66Y'** in a direction perpendicular to the Y direction of the XY stage.

As best illustrated in FIG. 4A, the arms **74** and **74'** and crossbar **76'** of the X follower **72** all lie within and move in the same plane crossing the Z axis. The center of gravity of the XY stage **30** lies within or is immediately adjacent to this plane. In this construction the drive forces from each of the drive coils **42X** and **42X'** are in a direction along the length of the arms **74** and **74'**, respectively. However, the arms **84** and **84'** of the Y follower **82** lie within and move in different parallel planes spaced apart along the Z axis from one another respectively above and below and parallel to the plane containing the X follower **72**. In the preferred embodiment, the crossbar **86** lies in the lower plane containing the arm **84'** and a spacer block **86'** is positioned between the overlapping ends of the arm **84** and crossbar **86** to space the arms **84** and **84'** in their respective parallel planes. As with X follower **72**, the drive forces from each of the drive coils **44Y** and **44Y'** are in a direction along the length of the arms **84** and **84'**. Also, predetermined gaps in X and Z directions are maintained between the drive coils **44Y(44Y')** and the drive tracks **88(88')** to achieve the guideless concept.

In operation of the guideless stage and isolated reaction frame of the present invention, the XY stage **30** is positioned in an initial position relative to the projection lens as sensed by the interferometer system **92**, and the XY stage **30** is supported in the desired Z direction from the object stage base **28** by the air bearings **36** with the drive coils **42X**, **42X'**, **44Y** and **44Y'** spaced from the drive elements in the form of drive tracks **78**, **78'**, **88** and **88'**, respectively. There is no direct contact between the XY stage **30** and the reaction frame **61**. That is, there is no path for the vibration of the reaction frame to affect the position of the XY stage and vice versa. There is only indirect contact via the transmission means that deliver the signals to the coils and the laser interferometer position sensing system which then transmits sensed position information to the controller which receives other commands to initiate drive signals which result in movement of the XY stage **30**.

With the known position of the XY stage **30** from the interferometer system **92**, drive signals are sent from the position control system **94** to the appropriate drive coils, **42X**, **42X'**, **44Y** and **44Y'** to drive the XY stage to a new desired position. The motion of the XY stage is sensed by the interferometer system **92** and position sensors **98X** and **98Y** (see FIG. 5), and the X follower **72** and Y follower **82** are driven by the drive members **77** and **87**, respectively, to follow the XY stage. As illustrated in FIG. 5, the position sensor **98X** detects a variation of the Y direction space between the XY stage **30** and the X follower **72** and generates an electric signal representing the amount of space to the position control system **94**. The position control system **94** generates a proper drive signal for the drive member **77** on the basis of the X position information from the interferometer system **92** and the signal from the position sensor **98X**.

Also, the position sensor **98Y** detects a variation of X direction space between the XY stage **30** and the Y follower **82** and generates an electric signal representing the amount of space, and the drive member **87** is energized on the basis of the Y position information from the interferometer system **92** and the signal from the position sensor **98Y**.

Yaw correction is accomplished by the pairs of linear motors which can be used to hold or offset yaw, or the pairs of linear motors can change the rotational position of the XY stage. The data from either or both pairs of laser beams **40A/40A'** and **40B/40B'** are used to obtain yaw information. Electronic subtraction of digital position data obtained from measurement using the laser beams **40A** and **40A'** or **40B** and **40B'** is performed or both differences are added and divided by two.

This invention allows the positioning function of the XY stage to be accomplished faster than if XY guides were used. Reaction forces created in moving the XY stage can be coupled away from the image forming optics and reticle handling equipment.

This invention needs no precision X or Y guides as compared to a guided stage, and precision assembly and adjustment of the wafer XY stage is reduced due to the lack of precision guides. The servo bandwidth is increased because the linear motor forces in the XY axes act directly on the wafer stage; they do not have to act through a guide system.

Forces from the XY linear motors can all be sent substantially through the center of gravity of the XY stage thereby eliminating unwanted moments of force (torque).

With the X follower **72** and the Y follower **82** mounted and moved totally independently of one another, any vibration of a follower is not conveyed to the wafer XY stage or to the optical system when using commercially available electro-magnetic linear motors for the magnetic coupling between each of the followers **72** and **82** and the XY stage **30** and with clearance between the coils and magnet drive tracks less than about 1 mm. Additionally, with the arms of one of the followers spaced above and below the arms of the other follower, the vector sum of the moments of force at the center of gravity of the XY stage due to the positioning forces of cooperating drive members is substantially equal to zero.

No connection exists between the XY stage and the follower stages that would allow vibrations to pass between them in the X, Y or θ degrees of freedom. This allows the follower stages to be mounted to a vibrating reference frame without affecting performance of the wafer stage. For example, if the reaction frame were struck by an object, the XY stage and the projection optical system would be unaffected.

It will be appreciated by a person skilled in the art that if the center of gravity is not equidistant between either of the two X drive coils or either of the two Y drive coils, that appropriate signals of differing magnitude would be sent to the respective coils to apply more force to the heavier side of the stage to drive the XY stage to the desired position.

For certain applications the drive elements **42X/42X'** or **42Y/42Y'** of the actuator or magnetic coupling assembly for supplying electro-magnetic force to the movable XY stage may be held stationary (see FIG. 5) in a static position with respect to movement of the stage in either the X or Y direction, respectively.

In the last of the explanation of this embodiment, referring to FIG. 1C again, the essential structure of the present invention will be described. As illustrated in FIG. 1C, the XY stage **30** is suspended on the flat smooth surface (parallel with the X-Y plane) of the stage base **28** through the air bearings **36** having air discharge ports and vacuum pre-load ports and is movable in X, Y and θ direction on the stage base **28** without any friction.

The stage base **28** is supported on the foundation (or ground, base structure) **21** by the isolation blocks **20**, arms

18, blocks 22, the vertical bars 26 and the horizontal bars 27. Each of the isolation blocks 20 is composed of a vibration absorbing assembly to prevent transmission of the vibration from the foundation 21.

Since FIG. 1C is a sectional view of the XY stage 30 along a line through the drive coils 42X, 42X' in Y direction, the following description is restricted about the X follower 72.

In FIG. 1C, the drive coils 42X are disposed in a magnetic field of drive track (magnet array elongated in X direction) 78 mounted on the follower arm 74 and the drive coils 42X' are disposed in a magnetic field of drive track 78' mounted on the follower arm 74'.

The two arms 74, 74' are rigidly assembled to move together in Y direction by the guide rails 69, 69' formed inside of the reaction frame 61. Also, the guide rails 69, 69' restrict the movement of the two arms 74, 74' in X and Z directions. And the reaction frame 61 is directly supported on the foundation 21 by the four support posts 62 independently from the stage base 28.

Therefore, the drive coils 42X(42X') and the drive tracks 78 (78') are disposed with respect to each other to maintain a predetermined gap (a few millimeters) in Y and Z directions.

Accordingly, when the drive coils 42X, 42X' are energized to move the XY stage 30 in X direction, the reaction force generated on the drive tracks 78, 78' is transferred to the foundation 21, not to the XY stage 30.

On the other hand, as the XY stage 30 moves in Y direction, the two arms 74, 74' are moved in Y direction by the drive member 77 such that each of the drive tracks 78, 78' follows respective coils 42X, 42X' to maintain the gap in Y direction on the basis of the measuring signal of the position sensor 98X.

While the present invention has been described with reference to the preferred embodiment having a pair of X drive members or coils 42X and 42X' and a pair of Y drive members or coils 44Y and 44Y', it is possible to construct a guideless stage and with an isolated reaction frame in accordance with the invention with just three drive members or linear motors such as shown in FIGS. 6 and 7. As illustrated in FIG. 6, a pair of Y drive coils 144Y and 144Y' are provided on the stage 130 and a single X drive coil or linear motor 142X is mounted centered at the center of gravity CG' of the XY stage. The Y drive coils 144Y and 144Y' are mounted on the arms 184 and 184' of the Y follower 182, and the X drive coil 144X is mounted on an arm 174' of a X follower 172. By applying appropriate drive signals to the drive coils 142X and 144Y and 144Y', the XY stage can be moved to the desired XY positions.

Referring now to FIGS. 8-11, there is shown an alternative embodiment of the present invention which includes links between the XY drive coils 242X, 242X', 244Y and 244Y' and the attachment to the XY stage 30'. These connections include a double flexure assembly 300 connecting the drive coil 244Y to one end of a connecting member 320 and a double flexure assembly 330 connecting the other end of the connecting member 320 to the XY stage 30'. The double flexure assembly 300 includes a flange 302 connected to the coil 244Y. A clamping member 304 is attached via clamping bolts to the flange 302 to clamp therebetween one edge of a horizontal flexible link 306. The other end of the flexible link 306 is clamped between two horizontal members 308 which are in turn integrally connected with a vertical flange 310 to which are bolted a pair of flange members 312 which clamp one edge of a vertical flexible member 314. The opposite edge of the vertical flexible

member 314 is clamped between a pair of flange members 316 which are in turn bolted to a flange plate 318 on one end of the connecting member 320. At the other end of the connecting member 320 a plate 348 is connected to two flange members 36 which are bolted together to clamp one end of a vertical flexible member 344. The opposite edge of the vertical member 344 is clamped by flange members 342 which are in turn connected to a plate 340 connected to a pair of clamping plates 338 clamping one edge of a horizontal flexible member 336, the opposing edge of which is in turn clamped onto the XY stage 30' with the aid of the plate 334. Thus, in each of the double flexure assemblies 300 and 330 vibrations are reduced by providing both a horizontal and a vertical flexible member. In each of these assemblies the vertical flexible members reduce X, Y and θ vibrations and the horizontal flexible members reduce Z, tilt and roll vibrations. Thus, there are eight vertical flex joints for X, Y and θ and eight horizontal flex joints for Z, tilt and roll.

As illustrated in FIG. 11, the coil 244Y is attached to a coil support 245Y which has an upper support plate 246 attached thereto which rides above the top of the magnetic track assembly 288. Vacuum pre-load type air bearings 290 are provided between the coil support 245Y and upper support plate 246 on the one hand and the magnetic track assembly 288 on the other hand.

In an operative example of the embodiment illustrated in FIGS. 8-11 the flexible members 306, 314, 344 and 336 are stainless steel 1 1/4" wide, 1/4" long and 0.012" thick with the primary direction of flex being in the direction of the thickness. In the embodiment illustrated members 306 and 314 are mounted in series with their respective primary direction of flex being orthogonal to one another; members 344 and 336 are similarly mounted.

While the present invention has been described in terms of the preferred embodiment, the invention can take many different forms and is only limited by the scope of the following claims.

I claim:

1. A stage assembly comprising:

a base;

a stage slidably movable on the base;

a reaction frame laterally surrounding the stage and supported independently of the base;

a first follower frame slidably movable on the reaction frame in a first direction; and

a second follower frame slidably movable on the reaction frame in a second direction orthogonal to the first direction;

wherein the stage is slidably movable along the first follower frame in the second direction and along the second follower frame in the first direction.

2. The stage assembly of claim 1, further comprising cooperating linear actuator elements mounted on the stage and on each of the first and second follower frames for positioning the stage along the first and second follower frames.

3. The stage assembly of claim 1, wherein a vector sum of the moments of force at the center of gravity of the stage due to positioning forces of the linear actuator elements mounted on the stage is substantially equal to zero.

4. The stage assembly of claim 1, wherein the first follower frame includes two-spaced apart arms located respectively in two parallel planes, with the center of gravity of the stage being therebetween.

5. The stage assembly of claim 1, further comprising two spaced-apart linear actuator elements mounted on the stage

9

and cooperating with two linear actuator elements mounted on the first follower frame for positioning the stage along the first follower frame, and at least one linear actuator element mounted on the stage cooperating with one linear actuator element mounted on the second follower frame for positioning the stage along the second follower frame.

6. The stage assembly of claim 1, further comprising a projection optical system for projecting an image onto the stage and being mounted to the base, and isolated mechanically from the reaction frame.

7. The stage assembly of claim 2, wherein each of the linear actuator elements mounted on the stage is a coil cooperating with a magnetic track mounted on one of the first and second follower frames, at least one of the coils being mounted to the stage by a double flexure including a first flexure element coupled to a perpendicularly arranged second flexure element, thereby reducing vibration.

8. The stage assembly of claim 1, further comprising a positioning system including:

a first sensor for sensing a position of the stage in the first direction and a second sensor for sensing a position of the stage in the second direction;

first means for driving the first follower frame on the reaction frame in the first direction;

second means for driving the second follower frame on the reaction frame in the second direction; and

means for controlling the first and second means for driving, in response to the sensed positions of the stage, wherein the means for controlling moves the first and second follower frames to within a predetermined distance of the stage, and without any direct physical contact between the stage and the first and second follower frames.

9. A method of positioning a stage on a base, comprising the steps of:

slidably driving the stage along each of two orthogonally arranged follower frames;

slidably driving both the follower frames relative to the base; and

supporting the follower frames independently of the base, thereby isolating the stage from reaction forces caused by the steps of driving.

10. An exposure apparatus for projecting a predetermined pattern image formed by a projection system onto a surface of a substrate supported on a stage member which is movable in two directions, said apparatus comprising:

10

(a) a base member for supporting said stage member to move in first and second directions on said base member;

(b) a column structure for holding said projection system and said base member together;

(c) an isolation assembly for supporting said column structure on a foundation;

(d) a reaction frame structure disposed around said base member and supported on said foundation independently from said isolation assembly;

(e) a first drive actuator for supplying a driving force to said stage member without contact, to move said stage member in the first direction on said base member, said first drive actuator being mounted to said reaction frame structure movably in the second direction; and

(f) a second drive actuator for moving said first drive actuator in the second direction on said reaction frame structure so as to follow movement of said stage member in the second direction on said base member.

11. An exposure apparatus according to claim 10, wherein said first drive actuator includes at least one linear motor having a first magnetizing unit fixedly mounted to said stage member and a second magnetizing unit provided on said reaction frame structure movably in the second direction, wherein said first and second magnetizing units interact with each other in a magnetic field.

12. An exposure apparatus according to claim 11, wherein said second drive actuator includes a linear motor having a third magnetizing unit fixedly mounted to said reaction frame structure and a fourth magnetizing unit fixedly connected to said second magnetizing unit.

13. An exposure apparatus according to claim 10, wherein said reaction frame structure includes a linear guide portion extending along the second direction, a movable frame member guided by said linear guide portion movably in the second direction within an upper space of said base member, and wherein said second drive actuator moves said movable frame member in the second direction.

14. An exposure apparatus according to claim 13, wherein said first drive actuator includes at least one linear motor having a first magnetizing unit fixedly mounted to said stage member and a second magnetizing unit fixedly mounted to said movable frame member so as to move relatively in the first direction.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 5,528,118
DATED : June 18, 1996
INVENTOR(S) : Martin E. Lee

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 6, line 19, delete "fin" and substitute--in--.

Signed and Sealed this

Twenty-second Day of October, 1996

Attest:



BRUCE LEHMAN

Attesting Officer

Commissioner of Patents and Trademarks